

DNG 1.1 – DINGate MultiMeter Communication module for MOD-bus sensors

The module is mains-powered and can be mounted in a standard DIN cabinet.



Product overview

The DNG – DINGate MultiMeter communication module is a DIN-sized communication module which enables remote readout of MOD-Bus sensors using LTE-M and / or NB-IoT. 16 devices with each 8 registers can be connected.

The module is mains-powered and can be mounted in a standard DIN cabinet. A slide-in slot on the front for the SIM card enables easy installation. The device has a standard SMA connector to mount an external antenna. Status indicators on the front panel provide users with visual indication of the module's operation. The optical interface on the side of the DNG – DINGate MultiMeter is used for onsite configuration. The communication with the MOD-Bus sensors is done using a 2-wire connection (RS485).

The unit supports the industry-standard protocol DLMS-COSEM for the WAN connection. This protocol enables also secure firmware update functionality.

The DNG – DINGate MultiMeter is ideal for companies looking for a cost-effective, easy-to-use and easy-to-manage compact remote readout solution for multiple types of sensor

Features

- LTE-M or NB-IoT WAN connectivity
- External antenna connector
- RTC backup
- DLMS WAN protocol
- Front panel SIM slide-in slot (2FF)
- Modbus over RS485

E info@xemex.eu
T +32 (0)3 201 95 95
W www.xemex.eu

NL Burgemeester Burgerslaan 40
5245 NH 's-Hertogenbosch
BE Metropoolstraat 11a
B2900 Schoten

Product Sheet
Versie 1.0

DNG 1.1 – DINGate
MultiMeter
communication
module

Technology

Physical Characteristics

- Housing: DIN 43880 / 2 units
- Weight: 106 gr
- Dimensions: 90 x 36 x 65 mm

Local interfaces

- RS485 (2-Wire + GND)
- Optical IR interface

WAN interface

- LTE-M: bands B3 (1800MHz) / B8 (900MHz) / B20 (800MHz)

Sim card connector

- Mini Sim (2FF) 25x15mm

Antenna connector

- SMA Female on housing

LED indicators

- Power / Meter connection indication
- WAN connection indication

Environmental Limits

- Operating Temperature: -20/+70°C
- Storage Temperature: -40/+70°C

Power requirements

- 230Vac/ 50 or 60Hz

Standards and Certifications

- Safety: IEC 60950-1
- EMC: EN 55016-2-3 EN 55016-2-1
EN 61000-3-2 EN 61000-3-3
EN 61000-4-2 EN 61000-4-3
EN 61000-4-4 EN 61000-4-5
EN 61000-4-6 EN 61000-4-11

E info@xemex.eu
T +32 (0)3 201 95 95
W www.xemex.eu

NL Burgemeester Burgerslaan 40
5245 NH 's-Hertogenbosch
BE Metropoolstraat 11a
B2900 Schoten